

## ROUTER AND ROUTE CONTROL METHOD


Publication number: JP2002141931  
Publication date: 2002-05-17  
Inventor: ISHIKAWA YUTAKA  
Applicant: SHARP KK  
Classification:  
- International: H04L12/56; H04L12/56; (IPC1-7): H04L12/56  
- European:  
Application number: JP20000330644 20001030  
Priority number(s): JP20000330644 20001030

[Report a data error here](#)

### Abstract of JP2002141931

**PROBLEM TO BE SOLVED:** To provide a router that conducts transfer of packets via networks at a low load by an IP header compression method and controls routing without confusing the packets with the same CID(Context ID) even outputted from nodes and to provide a route control method.

**SOLUTION:** The router is provided with a packet type discrimination means 101 that discriminates a packet type of a regular header, a full header and a compression header of an IP(Internet Protocol) header of a received packets from header information, a sender MAC(Media Access Control) address extract means 112, a destination IP address extract means 106 that extracts a destination IP address from the regular header, an IP address/CID extract means 105 that extracts a destination IP address/CID from the full header, a CID extract means 103 that extracts a CID from the compression header, a storage means 104 that stores a record of the sender MAC address extracted by the means 112 and the destination IP address CID extracted by the means 105 and assigns a specific number to the record, and a CID rewrite means 113 that rewrites the CID of the full header and the compression header into a specific number.



Data supplied from the [esp@cenet](#) database - Worldwide